

## SEMI-AUTOMATIC DIGITAL DISPLAY

### WHEEL BALANCER



#### smartSonar™

Automatic rim width detection using sonar sensors to avoid manual entry errors.



#### easyWeight™

Take the guesswork out of weight placement; this pinpoint accurate system uses a laser to show the exact spot to place a weight to ensure precise balancing.



#### **SPLIT WEIGHT MODE**

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.



#### **SEMI-AUTOMATIC DATA ENTRY**

Hand-operated gauge arm with easyALU™ assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.

# **B500P**



#### **TECHNICAL SPECIFICATIONS**

| Max Wheel Diameter | 42"   107cm                |
|--------------------|----------------------------|
| Max Wheel Weight   | 154 lbs.   70 kg           |
| Max Rim Width      | 20"   51cm                 |
| Power Supply       | 230V 50/60Hz               |
| Dimensions HxWxL   | 72"x34"x52"   183x87x131cm |

#### STANDARD ACCESSORIES

- · Three Centring Cone Set (42-116mm)
- · Weight Pliers
- · Adhesive Weight Remover
- · Clamping Cone with Rubber Cushion
- · Calibration Weight
- 4 Storage Pegs
- Power Clamp<sup>™</sup> Sleeve

#### **OPTIONAL ACCESSORIES**

- · Clamping Plate (200mm)
- Light Truck Kit Spacer and Cone (122-172mm)
- · Set of 9 Low-Taper Centring Collets (52.5-122mm)
- Basic Light Truck Cone Kit
- · Set of FP Quick Flange
- External Insulation Transformer



FIND A DISTRIBUTOR



