

TWO-POSTAUTOMOTIVE LIFT



THREE-STAGE FRONT & REAR ARMS

Accommodate a wide range of vehicles with our three-stage front and rear arms.



VERSATILE INSTALLATION OPTIONS

Installation is available in one of three height and width options to provide the most versatility for your shop's service needs; choose from 13.5-foot, 14-foot, or 14.5-foot height installation and 10-foot, 10.5-foot, or 11-foot width installation.



LOW-PROFILE URETHANE PADS

Low-maintenance, heavy-duty urethane pads are built to last and accommodate a wide range of manufacturer-recommended vehicle lifting points.



ADJUSTABLE HEIGHT EXTENSION

Increase your service capability to work on taller vehicles, including the largest trucks, SUVs, and cargo vans, with our two-foot column height extension.

16K 2-POST



TECHNICAL SPECIFICATIONS

Lifting Capacity	16,000 lbs. 7,257 kg
Configuration	Symmetric
Overall Width Options	155"/161"/167" 394/409/424cm
Overall Height Options	Standard: 162"/168"/174" 411/427/442cm Extended: 186"/192"/198" 472/488/503cm
Max Lifting Height	76"-82" 193-208cm
Lifting Time	62 seconds
Power Requirements	208-230V 60Hz 3HP 2.2kW
Air Supply Required	90-120 PSI 6-8 bar

STANDARD ACCESSORIES

 3-inch & 6-inch Stack Adapters and Organizer Racks

OPTIONAL ACCESSORIES

- 1-foot height extension
- 2-foot height extension





