

TWO-POSTAUTOMOTIVE LIFT



TWO-STAGE FRONT & REAR ARMS

Heavy-duty two-stage front and rear arms enable a wide range of symmetric lifting.



ADJUSTABLE HEIGHT EXTENSION

Increase your service capability to work on taller vehicles, including the largest trucks, SUVs, and cargo vans, with our two-foot column height extension.



N ADJUSTABLE URETHANE SCREW to pads

Heavy-duty polyurethane pad provides ample surface area to the vehicle frame and the telescoping feature provides simple access to factory-recommended lift points.



INCREASED CAPACITY FOR LARGER VEHICLES

Work on everything from a mini car to an RV with our high-capacity lift products for maximum revenue potential.



12K 2-POST



TECHNICAL SPECIFICATIONS

Lifting Capacity	12,000 lbs. 5,443 kg
Configuration	Symmetric
Overall Width	140" 356cm
Overall Height	Standard: 166"-175" 421-445cm Extended: 190"-199" 483-505cm
Max Lifting Height	78" 198cm
Lifting Time	61 seconds
Power Requirements	208-230V 60Hz 1Ph 30A 2HP 1.5kW
Air Supply Required	90-120 PSI 6-8 BAR

OPTIONAL ACCESSORIES

- Extension Adapter Kit: 3-inch x4 / 6-inch x2
- 24-inch Column Height Extension Kit
- Electric Vehicle (EV) Footpad Adapter
- Wide Frame Footpad Adapter
- Air/Electric Workstation w/Filter/Lubrication/Regulator
- 3 Phase 230 Volt





