## T7200

### ESSENTIAL FEATURES FAMILIAR DESIGN

We've combined classic design with modern features to make it easy for technicians of all levels to quickly and safely change tires with the John Bean® T7200 tire changer.

Utilizing a traditional swing-arm style with a center post clamp design, the John Bean T7200 offers speed and precision for efficient tirechanging operation. The on-floor hand-activated bead breaker shovel and roller board make quick work of the toughest tires, while an integrated wheel lift helps reduce technician fatigue and increase productivity. The center post clamp accommodates a wide range of wheel sizes and minimizes the chance of wheel damage, and the pneumatic bead assist enables efficient single-operator mounting and demounting of the upper bead. Our patented PROspeed™ technology monitors torque and optimizes the rotation speed to minimize the chance of tire damage throughout the operation.

For high-volume shops that need a tire changer with optimum technology; the T7200 is the machine for the job.



# **CENTER POST SWING-ARM** TIRE CHANGER



#### **CENTER POST CLAMP**

The center-post clamp design has numerous benefits, most important is the drastically reduced risk of wheel damage and less clamping restriction than the turntable design.



### **PROspeed™**

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.



### ON-FLOOR BEAD BREAKER (HAND-CONTROLLED)

Pneumatic assist control handle prevents shovel bounce-back with this on-floor bead breaker; the fastest solution for standard, soft sidewall, and high-aspect tires.



### PNEUMATIC BEAD ASSIST (OPTIONAL)

Our Pneumatic Bead Assist with a top roller is an exclusive, unique tool for the T7200 and makes it simple for a single technician to mount and demount OEM, low-profile, and highperformance tires.



# T7200

#### PNEUMATIC BEAD PUSHER

The Pneumatic Bead Pusher assists in the mounting process of the upper bead. Its dual-purpose design offers a reverse-side hook to help lift heavy tires.



#### **TOOL BOX**

The tool box provides a fixed storage area with four convenient shelves for tools, valves, and accessories.

### PNEUMATIC WHEEL LIFT WITH INTEGRATED ROLLER BOARD

The pedal-operated pneumatic wheel lift assists in lifting heavy wheels to reduce technician fatigue and increase productivity. The integrated roller board eases bead breaking.

### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	30"   76cm
Max Tire Width	15"   38cm
Max Wheel Diameter	44"   112cm
Wheel Lift Capability	154 lbs.   70 kg
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	85"x76"x74"   216x193x188cm

### STANDARD ACCESSORIES

- · Wave Plus Tire Lever & Sleeve
- · Plastic Rim Protector
- Bead Breaker Blade Protector
- · Lube Bucket
- Lube Bottle
- · Lube Brush
- Protective Insert for Mount/ Demount Head

### **OPTIONAL ACCESSORIES**

- Universal Reverse Mount Wheel Kit
- Bead Clamp



