B200S Small size big features

Designed to fit into a variety of shop sizes with a small footprint, the John Bean® B200S wheel balancer may be small in size but it gets the job done right.

Offering an easy-to-navigate interface and a raised monitor with colour display, the B200S helps technicians quickly and accurately balance wheels. Productivityenhancing features like smartSonar[™] and easyALU[™] allow users to measure wheels and quickly move through a balancing cycle.

Small in size with useful features, the John Bean B200S wheel balancer helps you keep profitable wheel service where it belongs: in your shop.



SEMI-AUTOMATIC MONITOR WHEEL BALANCER



smartSonar™ Automatic rim width detection using sonar sensors to avoid manual entry errors.



SEMI-AUTOMATIC DATA ENTRY

Hand-operated gauge arm with easyALU[™] assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.



SPLIT WEIGHT MODE

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.



QuickBAL™

Optimises the number of revolutions according to each wheel's specifications while always operating at maximum speed and reducing cycle time.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.



B200S



TECHNICAL SPECIFICATIONS

154 lbs. 70 kg
20" 51cm
230V 50/60Hz
2"x31"x40" 183x78x101cm
~

FRANCE

+33 134 48 58 78

STANDARD ACCESSORIES

- Three Centring Cone Set (42-116mm)
- Weight Pliers
- Adhesive Weight RemoverClamping Cone with Rubber
- Clamping Cone with Rubber
 Cushion
- Calibration Weight
- 4 Storage Pegs

ITALY

+39 0522 733 411


Quick Nut

OPTIONAL ACCESSORIES

- Light Truck Kit Spacer and Cone (122-172mm)
- Motorcycle Wheel Adaptor
- Clamping Plate (200mm)
- Set of 9 Low-Taper Centring Collets (52,5-122mm)
- FP Quick Flange for Manual Clamp for 4, 5, or 6-Stud Holes
- External Insulation Transformer

FIND A DISTRIBUTOR





GERMANY +49 8634 622 0

