## **TBD26** SUPREME VERSATILITY ULTIMATE PERFORMANCE

Work on a variety of heavy-duty tube-style, and tubeless tyres found on everything from buses to tractor-trailers with the John Bean<sup>®</sup> T8026.

The John Bean T8026 allows a single technician to work on tyres and OTR wheel assemblies up to 59 inches in maximum diameter and 27.5 inches in wheel diameter safely and easily, by utilizing a unique remote-control console.

Grip wheels with authority with a twospeed, self-centering, four-jaw, hydraulically operated chuck.

To boost productivity, we've designed the T8026 with a patented all-in-one bead breaker, mount and demount head assembly that makes quick work of even the toughest tyres.

Work smarter, not harder with the John Bean T8026.



## **HEAVY-DUTY** TYRE CHANGER



**MOBILE CONTROL UNIT** Wired remote control console allows one technician to safely monitor all tyre changing operations.



**NON-RETURN VALVE** A non-return safety valve prevents the chuck from opening in case of a sudden hydraulic pressure drop.



**BEAD BREAKER** The bead breaker disk is equipped with a special tilting system to assist bead breaking and ensure the disk is in the optimum position.



CHUCK

The self-centring hydraulic chuck is of solid design to accommodate wheels up to 1.000 kilograms (2.205 lbs).

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.



# **T8026**



### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	26"   66cm
Max Tyre Width	27"   69cm
Max Wheel Diameter	59"   150cm
Power Supply	400V 3ph 50Hz
Dimensions HxWxD	33"x66"x55"   84x167x140cm

### STANDARD ACCESSORIES OPTIONAL ACCESSORIES

- Wave Lever Plus
- Long Tyre Lever
- Mounting Clamp
- Jaw Protection Kit

ITALY +39 0522 733 411

- Standard Tyre Lever. 20" | 50cm
- Clamp for Light Alloy Rims
- Earth Mover Clamp (OTR)
- Tubeless Roller

FIND A DISTRIBUTOR





GERMANY +49 8634 622 0

