

T6000 BS PLUS

SIGNIFICANT UTILITY UNDENIABLE VALUE

Utilising a proven tilt-tower design, the John Bean® T6000 BS Plus is packed full of productivity-boosting features that help technicians get more work done with less effort.

Demounting and mounting tyres is a snap with an ergonomic, pedal-operated bead breaker and our advanced, three-piece pneumatic bead assist that makes mounting and demounting low profile tyres quick and simple.

Self-centring jaws with three manual adjustment positions securely clamp the wheel with the proper setup range. The pneumatic vertical arm provides quick and efficient positioning of the mounting head and the top-side bead seater quickly sets the bead with a high-speed blast of air.

WDK certified, and ready to become a crucial part of your shop's operations; the John Bean T6000 BS Plus is designed to allow technicians to work smarter, not harder.



TILT-TOWER TYRE CHANGER



TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



"PLUS" CONFIGURATION

Certified by WDK, the "Plus" models are equipped with Pneumatic Bead Assist and the "Plus" Accessories Kit to enable the correct mounting and demounting of UHP and run-flat tyres.



PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximises the rotation speed for safe, efficient operation.



TOP-SIDE BEAD SEATER

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.

JohnBean®

T6000 BS PLUS

TOOL BOX WITH INTEGRATED AIR PRESSURE GAUGE

The tool box provides a fixed storage area with four convenient shelves for tools, valves, and accessories, with an integrated air pressure gauge.

ADJUSTABLE CLAMPING JAWS

Self-centring nylon-covered clamping jaws protect the wheel and provide a secure grip.

PNEUMATIC VERTICAL ARM

Fast and ergonomic, the pneumatic vertical arm facilitates positioning of the mounting head on all wheels.

PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tyres.

ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



TECHNICAL SPECIFICATIONS

Max Rim Diameter	26" 66cm
Max Tyre Width	17" 43cm
Max Wheel Diameter	47" 120cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	76"x89"x68" 192x226x172cm

STANDARD ACCESSORIES

- Wave Lever Plus
- Wave Lever Plus Protector
- 5 kg Lube Bucket Holder
- Lube Brush
- Plastic Protectors for Mounting Head
- Jaw Protectors - Front & Rear
- Plastic Tyre Protector
- Rim Protection and String
- Bead Breaker Blade Protector
- Quick Exchange Device with Mounting Head
- "Plus" Kit

OPTIONAL ACCESSORIES

- Wheel Lift
- MH Tractor Kit
- 4" Jaws Adaptors for Centre Type Sliding Jaws
- Light Truck Adaptor for Centre Type Sliding Jaws
- 8" Motorcycle and ATV Adaptors for Centre-type Sliding Jaws

FIND A DISTRIBUTOR



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers, and tyre shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2022 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22276 (EU en) 07/2022

FRANCE
+33 134 48 58 78

GERMANY
+49 8634 622 0

ITALY
+39 0522 733 411

