

TWO-POSTAUTOMOTIVE LIFT



THREE-STAGE ARMS

Front and rear three-stage arms always allow perfect access to the pick-up points of the vehicle.



VERSYMMETRIC® TECHNOLOGY

Combining the advantages of an asymmetric and symmetric lift, Versymmetric Technology improves ergonomics when placing the arms to lift the car.



CARRIAGE CLEARANCE

The lifting carriage has a rugged design with integrated grease fitting and optimal door clearance with a rubber guard on the carriage to protect the car door.



FLEXIBLE INSTALLATION

The lift is available in two versions for your choice of height: low and high.

JLT 4500 S



TECHNICAL SPECIFICATIONS

Lifting Capacity	10.000 lbs. 4.500 kg
Configuration	Versymmetric®
Overall Width	142" 360cm
Overall Height	Standard: 156"-169" 395-430cm Extended: 181"-195" 460-495cm
Max Lifting Height	77,5" 197cm
Lifting Time	30 seconds
Power Requirements	400-415V 50Hz 3Ph
Air Supply Required	N/A

OPTIONAL ACCESSORIES

- Secondary Control Box
- Holder for Pick-Up Pad Adaptors
- Pick-Up Pad Extensions 3" | 7,5cm
- Energy Station Air Supply 230V 1Ph

FIND A DISTRIBUTOR





ITALY +39 0522 733 411



johnbean.com