JLT 3500 S SAFE PERFORMANCE EFFICIENT SERVICE

The John Bean® JLT 3500 Two-Post Lift provides versatility and convenience for service and repairs on vehicles up to 3,500 kilograms. This two-post lift is equipped with Versymmetric® technology to combine symmetric and asymmetric lift adjustments into one piece of equipment, bringing flexibility to any service bay and maximizing efficiency and shop space.

The JLT 3500 ensures the safe lifting of a wide range of vehicles, from passenger cars to SUVs and transporters with a standard roof height. And Versymmetric technology gives you the freedom to service all of these vehicles from the same service bay.




TWO-POST AUTOMOTIVE LIFT



THREE-STAGE ARMS

Front and rear three-stage arms always allow perfect access to the pick-up points of the vehicle.



VERSYMMETRIC® TECHNOLOGY

Combining the advantages of an asymmetric and symmetric lift, Versymmetric Technology improves ergonomics when placing the arms to lift the car.



CARRIAGE CLEARANCE

The lifting carriage has a rugged design with integrated grease fitting and optimal door clearance with a rubber guard on the carriage to protect the car door.



SHUT-OFF BAR

The safety shut-off bar prevents damage to the top of a vehicle, immediately stopping the lift when it is touched.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.



JLT 3500 S



TECHNICAL SPECIFICATIONS

Lifting Capacity	7.700 lbs. 3.500 kg
Configuration	Versymmetric®
Overall Width	Standard: 134" 341cm Wide: 140" 356cm
Overall Height	Standard: 154" 390cm Extended: 168" 427cm
Max Lifting Height	77,5" 197cm
Lifting Time	30 seconds
Power Requirements	400-415V 50Hz 3Ph
Air Supply Required	N/A

AUSTRIA +49 2641 24 5 24

FRANCE +33 134 48 58 78

OPTIONAL ACCESSORIES

- Extension Kit for JLT 3500 STD
- Secondary Control Box
- · Holder for Pick-Up Pad Adaptors
- Pick-up Pad Extensions 3" | 7,5cm
- Energy Station Air Supply 230V 1Ph





FIND A DISTRIBUTOR



GERMANY +49 8634 622 0