



JohnBear

1200°

BIZULP ULLY AUTOMATIC DIAGNOSTIC

WHEEL BALANCER

John Bean.



FULLY AUTOMATIC DIAGNOSTICWHEEL BALANCER







John Green	MORROLL STATE	2	anadhufus.	ARTERIOR CONT.
		Accessed 3 along 3 and dispressions		
THE REAL PROPERTY.	4000.00	200.00	APPROVED	100 mm (100 mm)
	STATE OF THE PARTY.			Total Bridge
and the same of th	-		the same of the	200.000
2010			100	
	200		No.	CHARLET & FRANCE
		MATERIA -		
Metale 1			Marine and base	terms from the country for or
			Contractor of Conceptual of	Trace on her
the state of the state of			State State State	and the sale
Name of Street	A		THE PERSON NAMED IN	
	600			
10		-	4"	1
-		-	1 -	
********			*******	
		-		
			MANAGEMENT.	
	_		4 -	
10			No.	
1			1	
			1	
~			********	
NAME OF TAXABLE PARTY.			September 1	
14-1			*	
		-		
10			No.	

RADIAL AND LATERAL RUNOUT

Provide a complete diagnosis of the assembly uniformity and display the radial and lateral runout measurements from the first to the third harmonic, indicating wheel assembly possibilities and pinpointing balancing issues.

AUTOMATIC SPOKE DETECTION

The laser scanner automatically detects the number and position of rim spokes for the system to indicate weight placement behind wheel spokes and allow for split weights.

easyWeight™

Take the guesswork out of weight placement; this pinpoint accurate system uses a laser to show the exact spot to place a weight to ensure precise balancing.

PRINTOUT

Reports can be printed through the local network or saved as a PDF to an external flash drive.

ADVANCED FEATURESPROFESSIONAL SERVICE



AUTOMATIC DATA ENTRY

No manual data entry is required; this machine automatically detects all the wheel dimensions and selects the balancing mode, weight type, and weight position to speed up the balancing cycle time and minimise operational errors.

SPLIT WEIGHT MODE

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.

STOP IN POSITION

Touch the screen to automatically rotate the wheel to the weight application position.

QuickBAL™

Optimises the number of revolutions according to each wheel's specifications while always operating at maximum speed and reducing cycle time.





B1200P

TECHNICAL SPECIFICATIONS

Max Wheel Diameter	42" 107cm
Max Wheel Weight	154 lbs. 70 kg
Max Rim Width	20" 51cm
Power Supply	230V 50/60Hz
Dimensions HxWxL	75"x39"x53" 190x100x136cm

STANDARD ACCESSORIES

- Three Centring Cone Set (42-116mm)
- Weight Pliers
- Adhesive Weight Remover
- Clamping Cone with Rubber Cushion
- Calibration Weight
- 4 Storage Pegs
- Power Clamp[™] Sleeve

OPTIONAL ACCESSORIES

- Light Truck Kit Spacer and Cone (122-172mm)
- Clamping Plate (200mm)
- Set of 9 Low-Taper Centring Collets (52,5-122mm)
- Set of FP Quick Flange Plates
- External Insulation Transformer
- Software Client PC Software "Network 2"



FIND A DISTRIBUTOR







GERMANY +49 8634 622 N ITALY +39 05*22 7*33 **4**11



johnbean.com