

# **SEMI-AUTOMATIC LASER MONITOR**WHEEL BALANCER



#### smartSonar™

Automatic rim width detection using sonar sensors to avoid manual entry errors.



## easyWeight<sup>™</sup>

Take the guesswork out of weight placement; this pinpoint accurate system uses a laser to show the exact spot to place a weight to ensure precise balancing.



## SPLIT WEIGHT MODE

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.



# **SEMI-AUTOMATIC DATA ENTRY**

Hand-operated gauge arm with easyALU™ assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.



# **B400L**

# **MONITOR AND INTEGRATED**

Raised monitor and weighttray-integrated touchpad for convenient operational control.



# **TECHNICAL SPECIFICATIONS**

| Max Wheel Diameter | 42"   107cm                |
|--------------------|----------------------------|
| Max Wheel Weight   | 154 lbs.   70 kg           |
| Max Rim Width      | 20"   51cm                 |
| Power Supply       | 230V 50/60Hz               |
| Dimensions HxWxL   | 72"x34"x52"   183x87x131cm |

+49 2641 24 5 24

## STANDARD ACCESSORIES

- · Three Centring Cone Set (42-116mm)
- · Weight Pliers
- · Adhesive Weight Remover
- · Clamping Cone with Rubber Cushion
- Calibration Weight
- 4 Storage Pegs
- Quick Nut

## **OPTIONAL ACCESSORIES**

- · Light Truck Kit Spacer and Cone (122-172mm)
- · Motorcycle Wheel Adaptor
- · Clamping Plate (200mm)
- · Set of 9 Low-Taper Centring Collets (52,5-122mm)
- FP Quick Flange for Manual Clamp for 4, 5, or 6-Stud Holes
- · External Insulation Transformer



FIND A DISTRIBUTOR













**johnbean**.com