## **T5600** Solid design dependable performance

The John Bean® T5600 works with large, heavy-duty commercial tyres to get the job done with ease. Built to work on the heavyduty truck, tractor, OTR wheel assemblies up to 90 inches in maximum diameter; clamping wheels of 44 inches or 56 inches diameter with optional extensions, the T5600 makes tough jobs easy.

Keeping operator safety in mind, the T5600 includes a non-return valve on the chuck that prevents it from opening should the unit experience a sudden drop in hydraulic pressure. The mobile control unit allows a single technician to efficiently, and safely monitor all tyre-changing operations remotely.

Durable construction and smart features make the T5600 the perfect choice for tyre changing service on heavy-duty wheels and tires.



## **HEAVY-DUTY** TYRE CHANGER



**MOBILE CONTROL UNIT** 

Wired remote control console allows one technician to safely monitor all tyre changing operations.



NON-RETURN VALVE

A non-return valve prevents the chuck from opening in case of a sudden hydraulic pressure drop.



**BEAD BREAKER** 

The bead breaker disk is equipped with a special tilting system to assist bead breaking and ensure the disk is in the optimum position.



CHUCK

The chuck is of solid design to accommodate wheels of up to 3,300 pounds (1,500 kg).

### WHEN GOOD ENOUGH ISN'T ENOUGH, JB.



# **T5600**



### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	44"   112cm
Max Tyre Width	43"   110cm
Max Wheel Diameter	90"   230cm
Power Supply	400V 3ph 50Hz
Dimensions HxWxD	42"x117"x81"   106x298x205cm

AUSTRIA +49 2641 24 5 24

### STANDARD ACCESSORIES

- Wave Lever Plus
- Long Tyre Lever
- Standard Tyre Lever
  20" | 50cm

GERMANY +49 8634 622 0

• Mounting Clamp


#### **OPTIONAL ACCESSORIES**

- Clamp for Light Alloy Rims
- Earth Mover Clamp (OTR)
- Clamping Extensions 32"-56" | 81-142cm
- Tubeless Roller

ITALY +39 0522 733 411







FRANCE +33 134 48 58 78

