

TWO-POSTAUTOMOTIVE LIFT



THREE-STAGE ARMS

Front and rear three-stage arms always allow perfect access to the pick-up points of the vehicle.



VERSYMMETRIC® TECHNOLOGY

Combining the advantages of an asymmetric and symmetric lift, Versymmetric Technology improves ergonomics when placing the arms to lift the car.



CARRIAGE CLEARANCE

The lifting carriage has a rugged design with integrated grease fitting and optimal door clearance with a rubber guard on the carriage to protect the car door.



SHUT-OFF BAR

The safety shut-off bar prevents damage to the top of a vehicle, immediately stopping the lift when it is touched.

JLT 3500 S



TECHNICAL SPECIFICATIONS

Lifting Capacity	7.700 lbs. 3.500 kg
Configuration	Versymmetric [®]
Overall Width	Standard: 134" 341cm Wide: 140" 356cm
Overall Height	Standard: 154" 390cm Extended: 168" 427cm
Max Lifting Height	77,5" 197cm
Lifting Time	30 seconds
Power Requirements	400-415V 50Hz 3Ph
Air Supply Required	N/A

OPTIONAL ACCESSORIES

- Extension Kit for JLT 3500 STD
- Secondary Control Box
- · Holder for Pick-Up Pad Adaptors
- Pick-up Pad Extensions 3" | 7,5cm
- Energy Station Air Supply 230V 1Ph





FRANCE +33 134 48 58 78 GERMANY +49 8634 622 N ITALY +39 0522 733 411

