B200S Small size big features

Designed to fit into a variety of shop sizes with a small footprint, the John Bean[®] B200S wheel balancer may be small in size but it gets the job done right.

Offering an easy-to-navigate interface and a raised monitor with colour display, the B200S helps technicians quickly and accurately balance wheels. Productivityenhancing features like smartSonar[™] and easyALU[™] allow users to measure wheels and quickly move through a balancing cycle.

Small in size with useful features, the John Bean B200S wheel balancer helps you keep profitable wheel service where it belongs: in your shop.



SEMI-AUTOMATIC MONITOR WHEEL BALANCER



smartSonar™ Automatic rim width detection using sonar sensors to avoid manual entry errors.



SEMI-AUTOMATIC DATA ENTRY

Hand-operated gauge arm with easyALU[™] assisted rim data entry for diameter and distance. Touch the rim with the gauge arm to enter the rim dimensions and automatically select the weight balancing mode.



SPLIT WEIGHT MODE

This feature allows for accurate balancing with easy-to-follow manual procedures to hide the weights behind the spokes, preserving the wheel's visual presentation.



QuickBAL™

Optimises the number of revolutions according to each wheel's specifications while always operating at maximum speed and reducing cycle time.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.



B200S



TECHNICAL SPECIFICATIONS

42" 107cm
154 lbs. 70 kg
20" 51cm
230V 50/60Hz
72"x31"x40" 183x78x101cm

AUSTRIA +43 2641 24 5 24

STANDARD ACCESSORIES

- Three Centring Cone Set (42-116mm)
- Weight Pliers
- Adhesive Weight Remover
- Clamping Cone with Rubber
 Cushion

GERMANY +49 8634 622 0

- Calibration Weight
- 4 Storage Pegs
- Quick Nut

OPTIONAL ACCESSORIES


- Light Truck Kit Spacer and Cone (122-172mm)
- Motorcycle Wheel Adaptor
- Clamping Plate (200mm)
- Set of 9 Low-Taper Centring Collets (52,5-122mm)
- FP Quick Flange for Manual Clamp for 4, 5, or 6-Stud Holes
- External Insulation Transformer

ITALY

+39 0522 733 411

FIND A DISTRIBUTOR





FRANCE

+33 134 48 58 78

