

# **TILT-TOWER**TYRE CHANGER



#### **TILT-TOWER**

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



#### PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximises the rotation speed for safe, efficient operation.



### ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



#### **TOP-SIDE BEAD SEATER**

This ergonomic hand-held nozzle injects a high-speed blast of air into the tyre to raise the bead and seal the tyre to the rim.

## T5325B 2S



#### **TECHNICAL SPECIFICATIONS**

Max Rim Diameter	24"   61cm
Max Tyre Width	13"   33cm
Max Wheel Diameter	39"   100cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	63"x73"x70"   160x185X178cm

#### STANDARD ACCESSORIES

- 5 kg Lube Bucket Holder
- · Lube Brush
- Bead Lever Plus
- Bead Lever Protector Plus
- Plastic Rim Protector. Clipon Type
- Bead Breaker Blade Sleeve
- Alloy Rim Protector Kit for Centre Type Sliding Jaws -Front & Rear

#### **OPTIONAL ACCESSORIES**

- Plastic Tyre Protector: Clip-on Type
- Smart Bead Spacer Tail
- Bead Clamp
- · Bead Press Tool MX
- Bead Pressing Roller for M/D
  Tool
- Quick Exchange Device with Mounting Head
- Wheel Lift



FIND A DISTRIBUTOR













**johnbean**.com