

Be **PRECISE**

T5540T

POWERFUL OPERATION PROFESSIONAL RESULTS

Boost productivity with features that allow technicians to get more work done in less time; the John Bean® T5540T is the ideal mix of design and innovation.

The tilt-tower design provides maximum operational clearance and self-centering jaws with three manual adjustment positions securely clamp the wheel with the proper setup range, the pneumatic vertical arm provides quick and efficient positioning of the mounting head while the exclusive PROspeed™ system automatically measures torque and manages speed during crucial tire-changing operations. Quickly break beads on all tire types with the ergonomically located pedal-controlled on-floor bead breaker.

To keep everything needed on hand to get the job done right, the T5540T includes a toolbox with an integrated pressure gauge and four shelves for easy storage of tools and accessories.

The T5540T tire changer is ready to boost your shop's productivity day after day.



TILT-TOWER TIRE CHANGER



TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tire on the turntable.



PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.



ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.



ADJUSTABLE CLAMPING JAWS

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

WHEN GOOD ENOUGH ISN'T ENOUGH, JB.

JohnBean

T5540T

TOOL BOX WITH INTEGRATED AIR PRESSURE GAUGE

The tool box provides a fixed storage area with four convenient shelves for tools, valves, and accessories, with an integrated air pressure gauge.

PNEUMATIC VERTICAL ARM

Fast and ergonomic, the pneumatic vertical arm facilitates positioning of the mounting head on all wheels.

TABLETOP BEAD SEATER

A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.



TECHNICAL SPECIFICATIONS

Max Rim Diameter	24" 61cm
Max Tire Width	15" 38cm
Max Wheel Diameter	39" 100cm
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	64"x66"x49" 162x169x126cm

STANDARD ACCESSORIES

- 5 kg Lube Bucket Holder
- Lube Brush
- Bead Breaker Blade Protector
- Jaw Protectors - Front & Rear
- Plastic Protectors for Mounting Head
- Rim Protection and String
- Wave Lever PLUS
- Wave Lever PLUS Protector

OPTIONAL ACCESSORIES

- Quick Exchange Device with Mounting Head
- Bead Breaker Blade for Off-Road Wheels
- Wheel Lift
- MH Tractor Kit
- 4-inch Jaw Adaptors for Centre Type Sliding Jaws
- Light Truck Adaptor for Centre Type Sliding Jaws
- 26-inch Motorcycle Adaptor Kit for Centre Type Sliding Jaws
- Motorcycle Mounting Head
- Motorcycle Bead Breaker Blade
- Slip-on Shoe
- Extension Bead Breaker Arm for Extra-Large Wheels
- Roller Board

FIND A DISTRIBUTOR



LATIN AMERICA
+1501 505 2794

Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tire shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2022 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22260 (LA en) 05/2022

