

AUTOMOTIVE LIFT SYSTEMS



EELR540A

Shown with optional FRL
(Light and air hose not included)



INDUSTRIAL STRENGTH LIFT SOLUTIONS.
PREMIUM FEATURES.

Unmatched productivity, performance and value.

INTRODUCING THE **18K** AUTOMOTIVE
LIFT SYSTEMS

JohnBean

STANDARD FEATURES

18K Two Post Lift Features

- Heavy-duty lifting capacity or 18,000 lbs (8,164kg)
- Oversized steel pulley reduces internal stress on equalization cables and provides increased durability
- Medium and high auxiliary adapters and storage brackets come standard
- Single point air actuated safety lock release - allows technician to disengage both columns simultaneously
- Tall 60" (152.4 cm) lifting carriages balance the long reaching 62" (157.48 cm) lift arms, optimizing load dispersment in column
- Standard combination stack screw pads accommodate a wide range of manufacturers' recommended vehicle pick up points
- Conforms with current ANSI/ALI ALCTV:2011 lift standard

Standard Accessories

- Two Organizer Racks for Adapter Storage
- Four U-Shaped Frame Truck Adapter
- Four Standard, Medium and Extended Height Adapters
- Four Reducer Bushings for Use With U-Shaped Frame Truck Adapters

EQUIPMENT SPECIFICATIONS

• Part Number:	EELR540A	EELR541A
• Capacity:	18,000 lbs (8,164kg)	18,000 lbs (8,164kg)
• Rise Height*:	85" (215.9 cm)	85" (215.9 cm)
• Overall Height:	174" (442 cm)	198" (502.9 cm)
• Floor to Overhead Shut Off:	167" (424.2 cm)	191" (485.1 cm)
• Overall Width:	154.75" (393.1 cm)	154.75" (393.1 cm)
• Drive Thru Width:	104.25" (264.8 cm)	104.25" (264.8 cm)
• Front and Rear Arm Reach:	38.5" - 62" (97.8 - 157.5 cm)	35.8" - 62" (97.8 0- 157.5 cm)
• Adj. Adapter, Lowered Pad Height**:	6.625" - 8.5" (16.8 - 21.6 cm)	6.625" - 8.5" (16.8 - 21.6 cm)
• Adj. Adapter, Medium Extension**:	10.625" - 12.5" (27 - 31.8 cm)	10.625" - 12.5" (27 - 31.8 cm)
• Adj. Adapter, High Extension**:	14.625" - 16" (36.8 - 37.1 cm)	14.625" - 16" (36.8 - 37.1 cm)
• Width Between Columns:	119.875" (304.5 cm)	119.875" (304.5 cm)
• Ceiling Height Requirement:	176" (447 cm)	200" (508 cm)
• Rise Time:	60 Seconds	60 Seconds
• Air Supply Required:	85 - 115 PSI (0.6 - 0.8 MPa)	85 - 115 PSI (0.6 - 0.8 MPa)
• Motor:	3 HP	3 HP
• Power Requirements***:	208 - 230V 1Ph 60Hz	208 - 230V 1Ph 60Hz
• Maximum Load per Arm:	4,500 lbs (2,041kg)	4,500 lbs (2,041kg)

*Rise height is measured with high extension

**Medium and high auxiliary adapter extensions are standard

***Optional three phase electrical also available, specify at time of order

For more information regarding the **18k Automotive Lifts**
call **800.362.4618 (US)** or **800.362.4608 (Canada)**
www.johnbean.com / www.johnbean.ca

John Bean is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2016 Snap-on Incorporated. All rights reserved. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All other marks are marks of their respective holders.

03/16 SS143413B

JohnBean®