

EELR538A



PROFESSIONAL AUTOMOTIVE LIFT SOLUTIONS. PREMIUM FEATURES.

Unmatched productivity, performance and value.

NTRODUCING THE **15K AUTOMOTIVE** LIFT SYSTEMS

JohnBean

STANDARD FEATURES

15K Two Post Lift Features

- 15, 000 lbs of heavy duty lifting power
- Symmetrical lifting with heavy duty arm restraint system
- Single point air actuated safety lock release allows the technician to disengage both columns simultaneously
- Tall 60" lifting carriages balance the long reaching 62" lift arms, optimizing load dispersement in column
- Standard combination stack screw pads accommodate a wide range of manufacturers' recommended vehicle pick up points. Includes four standard rubber coated screw pads, medium height extensions and high height extensions
- Oversized steel pulley reduces internal stress on equalization cables and provides increased durability
- Reduced floor loading with large column base footprint
- Padded overhead shut off system prevents vehicle damage from being raised too high
- Certified to the ANSI/ALI ALCTV:2011 automotive lift standard

15K Two Post Lift Optional Accessories

- Two Organizer Racks for Adapter Storage: EAK0327T01A
- Four U-Shaped Frame Truck Adapters: EAK0299T25A
- Four Reducer Bushings for use with U-Shaped Frame Truck Adapters: EAK0299T49A (To be used with EAK0299T25A)

EQUIPMENT SPECIFICATIONS

- Maximum Capacity:
- Rise Height*:
- Overall Height:
- Floor to Overhead Shut Off:
- Overall Width:
- Drive Thru Width:
- Front and Rear Arm Reach:
- Adj. Adapter, Lowered Pad Height:
- Adj. Adapter, Medium Extension**:
- Adj. Adapter, High Extension**:
- Width Between Columns:
- Ceiling Height Requirement:
- Rise Time:
- Air Supply Required:
- Motor:
- Power Requirements***:
- Max Load Per Arm:

EELR538A

15,000 lbs (6804kg)

85" (215.9cm)

174" (442cm)

167" (424.2cm)

154.75" (393.1cm)

104.25" (264.8cm)

38.5" - 62" (97.8 - 157.5cm)

14.625" - 16" (37 - 40.6cm)

119.875" (304.5cm)

176" (447cm)

<u>60 Seconds</u>

85 - 115 PSI

2 HP

208-230V 1Ph 60Hz

3,750 lbs (1701kg)

EELR539A

15,000 lbs (6804kg)

85" (215.9cm)

198" (502.9cm)

191" (485.1cm)

154.75" (393.1cm)

104.25" (264.8cm)

38.5" - 62" (97.8 - 157.5cm)

6.625" - 8.5" (16.8 - 21.6cm)

10.625" - 12.5" (27 - 31.8cm)

119.875" (304.5cm)

200" (508cm)

85 - 115 PSI

2 HP

208-230V 1Ph 60Hz

JohnBean

⁶⁰ Seconds

^{3,750} lbs (1701kg)

^{*}Rise height is measured with high extension

^{**}Medium & high auxiliary adapter extensions

^{***}Optional three phase electrical also available, specify at time of order