

TILT-TOWER TYRE CHANGER



TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tyre on the turntable.



PROspeed™

The innovative self-adjusting technology provides the optimum torque and maximizes the rotation speed for safe, efficient operation.



ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tyres.



PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tyres.

T5325



TECHNICAL SPECIFICATIONS

Max Rim Diameter	24" 61cm
Max Tyre Width	13" 33cm
Max Rim Width	12" 31cm
Max Wheel Diameter	39" 100cm
Wheel Lift Capability	154 lbs. 70 kg
Power Supply	230V 1ph 50-60Hz 16A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	63"x73"x70" 160x185X178cm

STANDARD ACCESSORIES OPTIONAL ACCESSORIES

- 5 kg Lube Bucket Holder
- Lube Brush
- Bead Lever Plus
- Bead Lever Protector Plus
- Plastic Rim Protector. Clip-on Type
- Bead Breaker Blade SleeveAlloy Rim Protector Kit for
- Alloy Rim Protector Kit for Center Type Sliding Jaws -Front & Rear
- Plastic Tyre Protector: Clip-on Type
- Smart Bead Spacer Tail
- Bead Clamp
- Bead Press Tool MX
- Bead Pressing Roller for M/D Tool
- Quick Exchange Device with Mounting Head
- Wheel Lift
- MH Tractor Kit
- 6-inch Jaw Adaptors for Centre Type Jaws
- Light Truck Adaptor for Centre Type Jaws
- · Slip-on Shoe
- Roller Board



FIND A DISTRIBUTOR



