

# SYSTEM V

## FULL-FEATURED CRITICAL PROTECTION

For high-volume shops that service OEM cars, SUV's, and light to medium truck applications, the John Bean® System V is a great addition to your workflow.

The pneumatically locking tilt-tower configuration easily moves out of the way to ergonomically allow placement of small to large wheels.

Once the tire is on the turntable, the self-adjusting four-jaw clamp secures the wheel clamps with power from twin cylinders.

Comprehensive pneumatic bead assist comes standard and provides an additional suite of features that make changing ultra-high performance and run-flat tires a snap.

Traditional design, with modern productivity-boosting features, makes the System V a great addition to your shop.

**Be FAST**



## TILT-TOWER TIRE CHANGER



### TILT-TOWER

The pneumatic Tilt-Tower post provides maximum clearance for installing the tire on the turntable.



### ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.



### TOOL BOX WITH INTEGRATED AIR PRESSURE GAUGE

The tool box provides a fixed storage area with four convenient shelves for tools, valves, and accessories, with an integrated air pressure gauge.



### ADJUSTABLE CLAMPING JAWS

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.

**WHEN GOOD ENOUGH ISN'T ENOUGH, JB.**

**JohnBean**

# SYSTEM V

## PNEUMATIC VERTICAL ARM

Fast and ergonomic, the pneumatic vertical arm facilitates positioning of the mounting head on all wheels.

## PNEUMATIC BEAD ASSIST

Our three-piece Pneumatic Bead Assist features a top roller, pressing foot, and lifting disk, to make it simple for a single technician to mount and demount low-profile and high-performance tires.

## TABLETOP BEAD SEATER

A direct burst of compressed air comes through the clamping jaws to facilitate bead seating.



## TECHNICAL SPECIFICATIONS

Max Rim Diameter	26"   66cm
Max Tire Width	17"   43cm
Max Wheel Diameter	47"   119cm
Power Supply	115V 1ph 60Hz 12A
Air Pressure Required	116-174 PSI   8-12 bar
Dimensions HxWxD	58"x65"x90"   147x165x229cm

## STANDARD ACCESSORIES

- Wave Plus Tire Lever
- Plastic Rim Protector
- Bead Breaker Blade Protector
- Lube Bucket
- Lube Brush
- Offset Mount/Demount Head Kit
- Protective Insert for Mount/Demount Head



Applies only to Canadian models:  
This product conforms to UL STD 201  
and is Certified to CSA STD C22.2 #68



UNITED STATES  
800.362.4618

CANADA  
800.362.4608



Snap-on® Total Shop Solutions offers a wide range of garage equipment solutions for workshops, garages, car dealers and tire shops, thanks to the specific solutions provided by its portfolio of premium brands. John Bean is a brand of TSS and is committed to product innovation and improvement. Therefore, specifications listed in this sell sheet may change without notice. ©2023 Snap-on Incorporated. John Bean is a trademark, registered in the United States and other countries, of Snap-on Incorporated. All rights reserved. All other marks are marks of their respective holders. sswH22024b (NA en) 03/2023

