

SWING-ARM TIRE CHANGER



SWING-ARM

The mounting arm swings to the side so that the machine can be installed in a space-saving way directly near a wall.



ADJUSTABLE CLAMPING JAWS

Self-centering nylon-covered clamping jaws protect the wheel and provide a secure grip.



ON-FLOOR BEAD BREAKER (PEDAL-OPERATED)

Traditional side-shovel bead breaker with ergonomic pedal-control positioned away from the shovel; the fastest solution for standard, soft sidewall, and high-aspect tires.



COLUMN-INTEGRATED AIR TANK

Unobtrusive, vertical design, column-integrated air tank helps conserve valuable shop space with a large volume for increased blasting capabilities.



SYSTEM II-E



TECHNICAL SPECIFICATIONS

Max Rim Diameter	24" 61cm
Max Tire Width	13" 33cm
Max Wheel Diameter	40" 100cm
Power Supply	115V 1ph 60Hz 12A
Air Pressure Required	116-174 PSI 8-12 bar
Dimensions HxWxD	71"x45"x55" 180x114x140cm

STANDARD ACCESSORIES

- · Wave Plus Tire Lever
- Lube Bucket
- Lube Brush
- Protective Insert for Mount/Demount Head
- · Plastic Jaw Protector



Applies only to Canadian models: This product conforms to UL STD 201 and is Certified to CSA STD C22.2 #68





